OFFICE OF THE MARION COUNTY SURVEYOR SECTION RECORD CORNER PARTY CHIEF: Wilcoxen CREV: -TYPE OF MARKER: Stone found 12" down METHOD OF ESTABLISHMENT: ____County: 9-25-89 FDM ties 0 Horino Ave 4000 S IN. S.P.C. E ZONE, NAD '83 15022621 Name: H 495447.9810(m) N: 47493.0030(m) E: 1-70 Section line 3750 S 4. 17.52

Good...down 15" w/guard pin : stone called 'c' and referenced by a 14" hickory S 60 W 46 links and a 14" hickory S 26 1/2 W 67 links per D.B. Hosbrook, County Surveyor on 3-1852 per Decatur Township Legal Survey Book . See: job #840100. Re-tied 8-25-05 by Wilcoxen.

(P*P) 3.

| D.C.C. | 150226 | |
|--------|----------|---|
| REF. | DISTANCE | DESCRIPTION |
| Ĺ | 216.29 | Mag nail w/brass washer top guard rail post |
| 2. | 156.02 | Mag nail w/brass washer W PwP#627-653 30"up |
| 3. | 102.69 | Mag nail w/brass washer F PwP#626-653 A 30"up |
| 4, | 17.52 | Cut 'x' S concrete post 3"up |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | + |